

From: Owen, Donnie D.
Sent: Wed Apr 14 21:43:37 2010
To: Clawson, Bryan R
Cc: Morel, Brian P; Lopez, Christopher
Subject: FW: 7" float collar
Importance: Normal
Attachments: 1366204 DOC041410.pdf

I have attached the ITEM DETAIL sheet for the 7" Centralizer Subs.

From: Clawson, Bryan R
Sent: Wednesday, April 14, 2010 4:33 PM
To: Lopez, Christopher; Owen, Donnie D.
Subject: Fw: 7" float collar

Guys, I need a favor. Please send spec for the 7 5/8 cent sub shipped bp macondo. Need asap. Bryan

From: Morel, Brian P <Brian.Morel@bp.com>
To: Clawson, Bryan R
Sent: Wed Apr 14 16:19:57 2010
Subject: RE: 7" float collar
Need 7" centralizer specs ASAP. Can you get them for me?

From: Clawson, Bryan R [mailto:bryan.clawson@weatherford.com]
Sent: Tuesday, April 13, 2010 12:04 PM
To: VH3@aol.com; Morel, Brian P
Subject: RE: 7" float collar

The minimum ID through the M45AP Float Collar is 1.45". The ID through the Landing Plate and the top of the Ball Cage is 2.347" With this in mind, the ball would sit on top of the Ball cage (See attached drawing with 1.75" ball on top of a M45 Float Collar) and then fluid would just be pumped around the ball. The flow area with the 1 5/8" ball on top of Cage will be 2.252"!

Regards,

Bryan Clawson
Weatherford Cementation Sales
Office: 281-260-1393
Cell: 713-823-2385
E-Mail: bryan.clawson@weatherford.com

From: VH3@aol.com [mailto:VH3@aol.com]
Sent: Tuesday, April 13, 2010 7:35 AM
To: Brian.Morel@bp.com



Cc: Clawson, Bryan R
Subject: Re: 7" float collar

In a message dated 4/12/2010 12:43:46 P.M. Central Daylight Time, Brian.Morcl@bp.com writes:
M45AP ball is caged

Any concerns about the Diverter closing ball (1-5/8") going thru or landing in the cage top of the FC and blocking circulation ?

Rgds,
Vernon Goodwin
Allamon Tool Co. Inc.
off 936-449-5433
mo 713-818-4067

CONFIDENTIAL & PRIVILEGED COMMUNICATION

The information contained in this message is privileged, confidential, and protected from disclosure.

This message is intended for the individual or entity addressed herein.

If you are not the intended recipient, please do not read, copy, use or disclose this communication to others.

Also please notify the sender by replying to this message, and then delete it from your system.

The sender totally disclaims, and will not accept, any responsibility or liability for the unauthorized use,

or the consequences of any unauthorized use, of this communication or message.

=====
CONFIDENTIAL & PRIVILEGED COMMUNICATION

The information contained in this message is privileged, confidential, and protected from disclosure.

This message is intended for the individual or entity addressed herein.

If you are not the intended recipient, please do not read, copy, use or disclose this communication to others.
Also please notify the sender by replying to this message, and then delete it from your system.
The sender totally disclaims, and will not accept, any responsibility or liability for the unauthorized use,
or the consequences of any unauthorized use, of this communication or message.

**Weatherford**

Item Information

Order



Item Number: 1366204
Description: Sub, CENT ROT 7 541R HCQ125 Hydril 513 32.0 10.75 OD
3rd Item Number: 541R070H513H12A005
Version: A
Price Book Reference: Manufacturing
Life Cycle State: Released

☐ Hide 0 Quantities

Find Similar Items

| Classification | Part Attributes |
|---|---|
| <input type="checkbox"/> Classification > Cementing > Casing accessories > Bow spring centralizer sub | <input type="checkbox"/> ASSY TYPE > Inseparable <input type="checkbox"/> BODY DIAMETER (in) > 7.179 <input type="checkbox"/> BOW SPRING MATERIAL > ALLOY STEEL <input type="checkbox"/> BOW SPRING QUANTITY > 4 <input type="checkbox"/> BOW SPRING TYPE > 36S <input type="checkbox"/> CASING SIZE (in) > 7.0 <input type="checkbox"/> CASING SIZE FRACTIONAL > 7 <input type="checkbox"/> CASING WEIGHT MAXIMUM (lbs-mass/ft) > 32.0 <input type="checkbox"/> CASING WEIGHT MINIMUM (lbs-mass/ft) > 32.0 <input type="checkbox"/> CASING WEIGHT RANGE > 32.00 <input type="checkbox"/> CONNECTION DOWN NAME > HYDL 513 <input type="checkbox"/> CONNECTION DOWN SIZE (in) > 7.0 <input type="checkbox"/> CONNECTION DOWN TYPE > PIN <input type="checkbox"/> CONNECTION DOWN WEIGHT (lbs-mass/ft) > 32.0 <input type="checkbox"/> CONNECTION UP NAME > HYDL 513 <input type="checkbox"/> CONNECTION UP SIZE (in) > 7.0 <input type="checkbox"/> CONNECTION UP TYPE > BOX <input type="checkbox"/> CONNECTION UP WEIGHT (lbs-mass/ft) > 32.0 <input type="checkbox"/> DEFAULT UOM > each <input type="checkbox"/> DRIFT DIAMETER (in) > 6.0 <input type="checkbox"/> DRILLOUT DIAMETER (in) > 6.024 <input type="checkbox"/> END BAND MATERIAL > CARBON STEEL <input type="checkbox"/> GENERIC DESCRIPTION (NODE SUB-GROUP) > CENTRALIZER SUB <input type="checkbox"/> INSIDE DIAMETER (in) > 6.024 <input type="checkbox"/> LENGTH (in) > 49.13 <input type="checkbox"/> LONG DESCRIPTION > SUB, CENTRALIZER ROTATING 7 541R HCQ125 HYDRIL 513 32.00 WITH 36S (.171) BOWS 10.750 OD, EXTRA LENGTH ON PIN AND BOX, NEXEN CENTRALIZER SUB REQ (MIN. WALL = .373"), DRIFT 6.000 <input type="checkbox"/> MATERIAL GRADE > HCQ125 <input type="checkbox"/> MAXIMUM OUTSIDE DIAMETER (in) > 10.75 <input type="checkbox"/> MAXIMUM RIGID OUTSIDE DIAMETER (in) > 7.5 <input type="checkbox"/> MODEL DESIGNATION > 541R |

<http://515endweb/EndecaWeb/nav/controller.asp?An=0&A=013662041027630%5FSPAC...> 4/14/2010

- ☐ PART NUMBER LEGACY > 541R070H513H12A005
- ☐ PRODUCT BURST RATING (psi) > 14160.0
- ☐ PRODUCT COLLAPSE RATING (psi) > 12540.0
- ☐ QUALITY LEVEL > NEXEN CENTRALIZER SUB REQUIREMENTS
- ☐ RESTRICTION SIZE (in) > 7.625
- ☐ SPECIAL REQUIREMENTS > EXTRA LENGTH ON PIN AND BOX, DRIFT 6.000, NEXEN CENTRALIZER SUB REQ (MIN. WALL = .373")
- ☐ TENSILE RATING (lbf) > 742000.0
- ☐ TYPE > ROTATING
- ☐ WELD SPECIFICATION > WW217

[Find Similar >>](#)[WindChill >>](#)[Drawings >>](#)[SROA Docs >>](#)[Companion Parts \(0\)](#)[New View](#)[Go Back](#)[Return Item](#)[Back to JDE](#)