

**Form MMS-124 - Electronic Version**  
**Application for Permit to Modify**

<b>Lease</b> G23018	<b>Area</b> AT	<b>Block</b> 138	<b>Well Name</b> 001	<b>ST</b> 00	<b>BP</b> 02	<b>Type</b> Exploratory
<b>Application Status</b> Approved		<b>Operator</b> 00078 Chevron U.S.A. Inc.				
<b>Pay.gov</b> <b>Amount:</b> \$110.00		<b>Agency</b> <b>Tracking ID:</b> EWL-APM-92098		<b>Pay.gov</b> <b>Tracking ID</b> 24UU6TDV		
<b>General Information</b>						
<b>API</b> 608184006802		<b>Approval Dt</b> 04-NOV-2008		<b>Approved By</b> Tom Meyer		
<b>Submitted Dt</b> 25-AUG-2008		<b>Well Status</b> Drilling Active		<b>Water Depth</b> 3480		
<b>Surface Lease</b> G23018		<b>Area</b> AT		<b>Block</b> 138		
<b>Approval Comments</b>						
<b>Correction Narrative</b>						
<b>Permit Primary Type</b> Abandonment Of Well Bore						
<b>Permit Subtype(s)</b> Permanent Abandonment						
<b>Operation Description</b>						
<b>Procedural Narrative</b>						
<p>1. Note: Well has been drilled to a total depth of 29,500' MD / 29,495' TVD. P/U 9 3/8" EZSV and TIH on drill pipe. Set EZSV @ 24,580'. Sting in and establish injection pressure. Squeeze cement below EZSV to provide cement coverage in the open hole 100' below the 9-3/8" shoe @ 24,676'. Sting out and place 100' of cement on top of the EZSV. POOH to 24,268' and circulate 1.5 drill pipe volumes.</p> <p>2. Continue to POOH laying down drill pipe. C&amp;C mud. Place cement plug across 9-3/8" liner top from 21,775' (100' below TOL) to 21,575' (100' above TOL). POOH to 21,257' and circulate 1.5 drill pipe volumes.</p> <p>3. Continue to POOH laying down drill pipe. C&amp;C mud. Place cement plug across 11-7/8" liner top from 20,536' (100' below TOL) to 20,336' (100' above TOL). POOH to 20,064' and circulate 1.5 drill pipe volumes.</p> <p>4. Continue to POOH laying down drill pipe. C&amp;C mud. Place cement plug across 13-5/8" liner top from 15,326' (100' below TOL) to 15,126' (100' above TOL). POOH to 14,889' and circulate 1.5 drill pipe volumes.</p> <p>5. Continue to POOH laying down drill pipe. C&amp;C mud. Pressure test cement plug on 13-5/8" liner top to 1000 psi for 15 minutes. Place cement plug in 16" casing from 3800' to 4100'. Pressure test cement plug @ 3800' to 1000 psi for 15 minutes. Conduct negative test on cement plug @ 3800' to 1500 psi for 15 minutes (differential between 16.2 ppg SBM and 8.6 ppg SW). Displace to seawater. POOH and L/D EZSV running tool.</p> <p>6. RIH with wear sleeve retrieval tool and riser brush. Pull wear sleeve. POOH and L/D wear sleeve and riser brush.</p> <p>7. R/U riser handling tools. Unlatch BOP stack. Pull riser and BOP.</p>						

**Form MMS-124 - Electronic Version**  
**Application for Permit to Modify**

<b>Lease</b> G23018	<b>Area</b> AT	<b>Block</b> 138	<b>Well Name</b> 001	<b>ST</b> 00	<b>BP</b> 02	<b>Type</b> Exploratory
<b>Application Status</b> Approved		<b>Operator</b> 00078 Chevron U.S.A. Inc.				
<p>8. Run drill pipe in open water to place cement plug across 16" liner top from 3686' (100' below TOL) to 3536' (50' above TOL). Pull drill pipe and lay down same.</p> <p>9. ROV to install P&amp;A cap on wellhead.</p>						
<b>Subsurface Safety Valve</b> <b>Type Installed</b> N/A <b>Feet below Mudline</b>						
<b>Shut-In Tubing Pressure (psi)</b>						
<b>Rig Information</b>						
<b>Name</b>	<b>Id</b>	<b>Type</b>	<b>ABS Date</b>	<b>Coast Guard Date</b>		
ENSCO 7500	99908	SEMISUBMERSIBLE	31-DEC-2010	10-FEB-2011		
<b>Blowout Preventers</b>						
<b>Preventer</b>	<b>Size</b>	<b>Working Pressure</b>	<b>--- Test Pressure ---</b>			
			<b>Low</b>	<b>High</b>		
Rams	18.75	15000	250	11400		
Annular		10000	250	7000		
Coil Tubing		0	0	0		
Snubbing		0	0	0		
Wireline		0		0		
<b>Date Commencing Work (mm/dd/yyyy)</b> 26-AUG-2008						
<b>Estimated duration of the operation (days)</b> 12						
<b>Verbal Approval Information</b>						
<b>Official</b>			<b>Date (mm/dd/yyyy)</b>			
David Trocquet			24-AUG-2008			
<b>Questions</b>						
<b>Number</b>	<b>Question</b>	<b>Response</b>	<b>Response Text</b>			
1	Is H2S present in the well? If yes, then comment on the inclusion of a Contingency Plan for this operation.	NO				
2	Is this proposed operation the only lease holding activity for the subject lease? If yes, then comment.	NO				
3	Will all wells in the well bay and related production equipment be shut-in when moving on to or off of an offshore platform, or from well to well on the platform? If not, please explain.	N/A				

**Form MMS-124 - Electronic Version**  
**Application for Permit to Modify**

<b>Lease</b> G23018	<b>Area</b> AT	<b>Block</b> 138	<b>Well Name</b> 001	<b>ST</b> 00	<b>BP</b> 02	<b>Type</b> Exploratory
<b>Application Status</b> Approved		<b>Operator</b> 00078 Chevron U.S.A. Inc.				

**Questions**

Number	Question	Response	Response Text
4	Are you downhole commingling two or more reservoirs?	N/A	
5	Will the completed interval be within 500 feet of a lease or unit boundary line? If yes, then comment.	N/A	
6	For permanent abandonment, will casings be cut 15 feet below the mudline? If no, then comment.	NO	Permission is requested for a departure from 30 CFR 250.1716 (b)(3) Removal of wellheads and casings. The wellhead will be left in place. The water depth is 3,480'.

**ATTACHMENTS**

File Type	File Description
pdf	Proposed Wellbore Schematic

**CONTACTS**

<b>Name</b>	John Connor
<b>Company</b>	Chevron U.S.A. Inc.
<b>Phone Number</b>	832-854-3659
<b>E-mail Address</b>	JohnConnor@chevron.com
<b>Contact Description</b>	Drilling Superintendent Christine Beiriger Chevron U.S.A. Inc. 832-854-4012 cbei@chevron.com Operations Engineer Debbie Campise Chevron U.S.A. Inc. 832-854-2617 cmps@chevron.com Drilling Engr. Asst. Tri Karunoputro Chevron U.S.A. Inc. 832-854-4695 trikaru@chevron.com Operations Engineer

**Form MMS-124 - Electronic Version**  
**Application for Permit to Modify**

---

PAPERWORK REDUCTION ACT OF 1995 (PRA) STATEMENT: The PRA (44 U.S.C. 3501 et seq. Requires us to inform you that we collect this information to obtain knowledge of equipment and procedures to be used in drilling operations. MMS uses the information to evaluate and approve or disapprove the adequacy of the equipment and/or procedures to safely perform the proposed drilling operation. Responses are mandatory (43 U.S.C. 1334). Proprietary data are covered under 30 CFR 250.196. An agency may not conduct or sponsor, and a person is not required to respond to, a collection of information unless it displays a currently valid OMB Control Number. Public reporting burden for this form is estimated to average 11/4 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to the Information Collection Clearance Officer, Mail Stop 4230, Minerals Management Service, 1849 C Street, N.W., Washington, DC 20240.