


# Cajun Express

Water Depth	6,909'
RKB to Wellhead	6,981'

Client	Chevron USA
Well	OCS-G 18753 Well 001

Elevation from Datum  
to Center of Packer



Note: Ram block height is 11.5 inches  
Annular Packer height is 18 inches  
All Measurements are in feet.

## 6.1 Diverter

• Manufacturer	: HYDRIL
• Type	: FS 21-500
• Maximum opening	: 59"1/2
• Packer internal diameter	: 21"
• Working pressure	: 500 psi
• Seal off range	: 13-3/8" to complete shutoff
• Operating fluid mixture	: Water based soluble oil
• Overboard lines size overboard)	: 12" (starboard and port overboard)

- ⇒ One vent line 12" equipped with Flow Selector (always "open") to starboard or port overboard.
- ⇒ The diverter main line is equipped with a 6" return line connected to the Poorboy Mud Gas Separator and a 12" hydraulically actuated ball valve. This 6" line is also fitted with a 6" hydraulically actuated ball valve as shown in Fig. Xx. These two valves are interlocked so that at any time, one of the valves is opened and the other is closed. This function is activated from the WCC and the panel indicates clearly the "open-close" status of each valve.
- ⇒ The Diverter Control Panel are located locally at the HPU, remotely in the WCC and Offshore Manager's office.




Fig. xx - 6" Line from Diverter Overboard to Poorboy MGS

