

From: Mix, Kurt [Kurt.Mix@bp.com]
Sent: Friday, April 23, 2010 12:39 PM
To: William Burch
Subject: Emailing: Macondo_Seafloor_Blowout_DP.dml,
Macondo_Seafloor_Blowout_DP_Dropped.dml,
Macondo_Seafloor_Blowout_Behind_Casing.dml
Attachments: Macondo_Seafloor_Blowout_DP.dml; Macondo_Seafloor_Blowout_DP_Dropped.dml;
Macondo_Seafloor_Blowout_Behind_Casing.dml

<<Macondo_Seafloor_Blowout_DP.dml>> <<Macondo_Seafloor_Blowout_DP_Dropped.dml>>
<<Macondo_Seafloor_Blowout_Behind_Casing.dml>>

The message is ready to be sent with the following file or link attachments:

Macondo_Seafloor_Blowout_DP.dml
Macondo_Seafloor_Blowout_DP_Dropped.dml
Macondo_Seafloor_Blowout_Behind_Casing.dml

Note: To protect against computer viruses, e-mail programs may prevent sending or receiving certain types of file attachments. Check your e-mail security settings to determine how attachments are handled.



```

<?xml version="1.0" encoding="UTF-8" ?>
<!-- Created by Liquid XML 2008 (www.liquid-technologies.com) for Scandpower Petroleum
Technology -->
- <Project xmlns:xs="http://www.w3.org/2001/XMLSchema-instance" Version="2.0">
- <Case>
- <CaseDescription>
  <CompanyName>BP GoM Deepwater Exploration</CompanyName>
  <ProjectName>Macondo</ProjectName>
  <FieldName>Macondo Prospect - OCS-G-32306</FieldName>
  <RigName>TO Deepwater Horizon</RigName>
  <WellName>MC 252 #1</WellName>
  <WellSectionName />
  <Date>2010-04-21</Date>
  <CreatorName>Kurt Mix</CreatorName>
  <Description>Simulation runs to support on going operations. Original Mud at time of
  incident is seawater in the riser and sobm in the hole. The equivalent pressure at
  td is 11937 psi at 18360' tvd equals 12.5 ppg. Data Gathered from Tiger Team Pore
  Pressure version 7 dated 3/16/2010. Adjusted reservoir pressure to 10255 psi by
  reducing the original reservoir pressure by a 0.3 psi/ft light oil gradient. This run
  has added a 2245 psi back pressure to account for the seawater column.
  KEM</Description>
</CaseDescription>
- <Well>
  <SteelRoughness>0.0018</SteelRoughness>
  <OpenHoleRoughness>0.1</OpenHoleRoughness>
  <IsShutIn>false</IsShutIn>
  <WellHeadPressure>NaN</WellHeadPressure>
  <UseFluidBoundary>false</UseFluidBoundary>
  <FluidBoundary>NaN</FluidBoundary>
  <UseWellHeadPressure>false</UseWellHeadPressure>
- <InjectionSystem>
  <CheckValveInstalled>false</CheckValveInstalled>
- <DrillstringInjection>
  <Active>false</Active>
  <FlowStopSubOn>false</FlowStopSubOn>
  <FlowStopSubPressure>NaN</FlowStopSubPressure>
  <FlowStopSubPosition>NaN</FlowStopSubPosition>
  <FlowStopSubVelocity>NaN</FlowStopSubVelocity>
- <Gas>
  <Density>0.7167</Density>
  <N2>0</N2>
  <CO2>0</CO2>
  <H2S>0</H2S>
  <Hydrocarbon>1</Hydrocarbon>
  <MassFraction>NaN</MassFraction>
</Gas>
</DrillstringInjection>
- <AnnulusInjection>
  <Active>true</Active>
  <InjectionSystemType>Parasite annulus</InjectionSystemType>
  <InjectionFluidType>Gas</InjectionFluidType>
  <InjectionDepth>3962.4</InjectionDepth>
  <KillFluidDensity>NaN</KillFluidDensity>
  <KillFluidViscosity>0.007</KillFluidViscosity>
  <LiquidRateChange>0.00084120240000000001</LiquidRateChange>
  <VolumetricOutput>NaN</VolumetricOutput>
- <ParasiteString xs:type="Casing">
  <Name />
  <Description />

```

WW-MDL-00071354

```

    <InnerDiameter>0.16002</InnerDiameter>
    <OuterDiameter>NaN</OuterDiameter>
    <Length>4572</Length>
    <EffectiveDiameter>NaN</EffectiveDiameter>
    <WeightPerLength>NaN</WeightPerLength>
    <Emodulus>210000000000</Emodulus>
    <YieldStrength>NaN</YieldStrength>
    <YieldStress>482700000</YieldStress>
  - <Thermophysical>
    <Density>NaN</Density>
    <DensityGradient>NaN</DensityGradient>
    <ThermalConductivity>NaN</ThermalConductivity>
    <ThermalConductivityGradient>NaN</ThermalConductivityGradient>
    <SpecificHeat>NaN</SpecificHeat>
    <SpecificHeatGradient>NaN</SpecificHeatGradient>
    <UseCustomThermalConductivity>false</UseCustomThermalConductivity>
    <UseCustomSpecificHeat>false</UseCustomSpecificHeat>
    <UseCustomDensity>false</UseCustomDensity>
  </Thermophysical>
</ParasiteString>
- <Gas>
  <Density>0.7167</Density>
  <N2>0</N2>
  <CO2>0</CO2>
  <H2S>0</H2S>
  <Hydrocarbon>1</Hydrocarbon>
  <MassFraction>NaN</MassFraction>
</Gas>
  <PressureLoss>NaN</PressureLoss>
</AnnulusInjection>
</InjectionSystem>
- <Survey>
  <DataExpansionType>Unexpanded</DataExpansionType>
  - <SurveySection>
    <Md>0</Md>
    <Inclination>0</Inclination>
    <Azimuth>0</Azimuth>
  </SurveySection>
  - <SurveySection>
    <Md>5596.1280000000001</Md>
    <Inclination>0</Inclination>
    <Azimuth>0</Azimuth>
  </SurveySection>
</Survey>
- <Drillstring>
  <DrillstringType>Drillpipe</DrillstringType>
  <AverageStandLength>NaN</AverageStandLength>
  <UseTooljoints>false</UseTooljoints>
  <UseCentralizers>false</UseCentralizers>
  <TravellingAssemblyWeight>NaN</TravellingAssemblyWeight>
  - <SnubbingUnit>
    <StripperFrictionForce>NaN</StripperFrictionForce>
    <SurfaceBucklingLength>NaN</SurfaceBucklingLength>
    <Active>false</Active>
  - <GuideTube>
    <Name />
    <Description />
    <InnerDiameter>NaN</InnerDiameter>

```

```

    <Length>NaN</Length>
    <Active>false</Active>
  </GuideTube>
</SnubbingUnit>
- <Tubular>
  <UseRoller>false</UseRoller>
  <IsStiffElement>false</IsStiffElement>
  <SectionLength>243.84</SectionLength>
  - <TubularComponent xs:type="Drillpipe">
    <Name>dp 3 1/2" S135 15.50 lb/ft</Name>
    <Description />
    <InnerDiameter>0.066100000000000001</InnerDiameter>
    <OuterDiameter>0.088900000000000001</OuterDiameter>
    <Length>10</Length>
    <EffectiveDiameter>NaN</EffectiveDiameter>
    <WeightPerLength>23.066542</WeightPerLength>
    <Emodulus>210000000000</Emodulus>
    <YieldStrength>NaN</YieldStrength>
    <YieldStress>930100000</YieldStress>
  - <Thermophysical>
    <Density>7840</Density>
    <DensityGradient>0</DensityGradient>
    <ThermalConductivity>48</ThermalConductivity>
    <ThermalConductivityGradient>0</ThermalConductivityGradient>
    <SpecificHeat>500</SpecificHeat>
    <SpecificHeatGradient>0</SpecificHeatGradient>
    <UseCustomThermalConductivity>true</UseCustomThermalConductivity>
    <UseCustomSpecificHeat>true</UseCustomSpecificHeat>
    <UseCustomDensity>true</UseCustomDensity>
  </Thermophysical>
  <JointInnerDiameter>0.05715</JointInnerDiameter>
  <JointOuterDiameter>0.1397</JointOuterDiameter>
  <JointsPerStand>1</JointsPerStand>
</TubularComponent>
- <Centralizer>
  <Spacing>NaN</Spacing>
  <MinOuterDiameter>NaN</MinOuterDiameter>
  <MaxOuterDiameter>NaN</MaxOuterDiameter>
  <RestoringForce>NaN</RestoringForce>
  <Standoff>NaN</Standoff>
</Centralizer>
</Tubular>
- <Tubular>
  <UseRoller>false</UseRoller>
  <IsStiffElement>false</IsStiffElement>
  <SectionLength>2040.636</SectionLength>
  - <TubularComponent xs:type="Drillpipe">
    <Name>dp 5 1/2" S135 21.90 lb/ft</Name>
    <Description />
    <InnerDiameter>0.1214</InnerDiameter>
    <OuterDiameter>0.1397</OuterDiameter>
    <Length>10</Length>
    <EffectiveDiameter>NaN</EffectiveDiameter>
    <WeightPerLength>32.5907916</WeightPerLength>
    <Emodulus>210000000000</Emodulus>
    <YieldStrength>NaN</YieldStrength>
    <YieldStress>930000000</YieldStress>
  - <Thermophysical>

```

```

    <Density>7840</Density>
    <DensityGradient>0</DensityGradient>
    <ThermalConductivity>48</ThermalConductivity>
    <ThermalConductivityGradient>0</ThermalConductivityGradient>
    <SpecificHeat>500</SpecificHeat>
    <SpecificHeatGradient>0</SpecificHeatGradient>
    <UseCustomThermalConductivity>true</UseCustomThermalConductivity>
    <UseCustomSpecificHeat>true</UseCustomSpecificHeat>
    <UseCustomDensity>true</UseCustomDensity>
  </Thermophysical>
  <JointInnerDiameter>0.0762</JointInnerDiameter>
  <JointOuterDiameter>0.1905</JointOuterDiameter>
  <JointsPerStand>1</JointsPerStand>
</TubularComponent>
- <Centralizer>
  <Spacing>NaN</Spacing>
  <MinOuterDiameter>NaN</MinOuterDiameter>
  <MaxOuterDiameter>NaN</MaxOuterDiameter>
  <RestoringForce>NaN</RestoringForce>
  <Standoff>NaN</Standoff>
</Centralizer>
</Tubular>
- <ElementAtEnd>
  <UseRoller>false</UseRoller>
  <IsStiffElement>false</IsStiffElement>
  <SectionLength>NaN</SectionLength>
- <TubularComponent xs:type="Bit">
  <Name>Bit 8 1/2 pdc</Name>
  <Description />
  <InnerDiameter>NaN</InnerDiameter>
  <OuterDiameter>0.1547876</OuterDiameter>
  <Length>NaN</Length>
  <EffectiveDiameter>NaN</EffectiveDiameter>
  <WeightPerLength>NaN</WeightPerLength>
  <Emodulus>210000000000</Emodulus>
  <YieldStrength>NaN</YieldStrength>
  <YieldStress>482700000</YieldStress>
- <Thermophysical>
  <Density>7840</Density>
  <DensityGradient>NaN</DensityGradient>
  <ThermalConductivity>48</ThermalConductivity>
  <ThermalConductivityGradient>NaN</ThermalConductivityGradient>
  <SpecificHeat>500</SpecificHeat>
  <SpecificHeatGradient>NaN</SpecificHeatGradient>
  <UseCustomThermalConductivity>false</UseCustomThermalConductivity>
  <UseCustomSpecificHeat>false</UseCustomSpecificHeat>
  <UseCustomDensity>false</UseCustomDensity>
</Thermophysical>
  <FlowArea>0.00045</FlowArea>
- <FlowRateRange>
  <Min>NaN</Min>
  <Max>NaN</Max>
  <Steps>0</Steps>
</FlowRateRange>
- <RpmRange>
  <Min>NaN</Min>
  <Max>NaN</Max>
  <Steps>0</Steps>

```

```

    </RpmRange>
    <NozzleDiameter>0.0119</NozzleDiameter>
    <NozzleDiameter>0.0119</NozzleDiameter>
    <NozzleDiameter>0.0119</NozzleDiameter>
    <NozzleDiameter>0.0119</NozzleDiameter>
    <FlowAreaType>Total flow area</FlowAreaType>
  </TubularComponent>
- <Centralizer>
  <Spacing>NaN</Spacing>
  <MinOuterDiameter>NaN</MinOuterDiameter>
  <MaxOuterDiameter>NaN</MaxOuterDiameter>
  <RestoringForce>NaN</RestoringForce>
  <Standoff>NaN</Standoff>
</Centralizer>
</ElementAtEnd>
- <Eccentricity>
  <EccentricityType>Not used</EccentricityType>
</Eccentricity>
</Drillstring>
- <WellboreGeometry>
- <Riser>
  <Name />
  <Description />
  <InnerDiameter>NaN</InnerDiameter>
  <OuterDiameter>NaN</OuterDiameter>
  <Length>NaN</Length>
  <EffectiveDiameter>NaN</EffectiveDiameter>
  <WeightPerLength>0</WeightPerLength>
  <Emodulus>210000000000</Emodulus>
  <YieldStrength>NaN</YieldStrength>
  <YieldStress>482700000</YieldStress>
- <Thermophysical>
  <Density>7840</Density>
  <DensityGradient>0</DensityGradient>
  <ThermalConductivity>48</ThermalConductivity>
  <ThermalConductivityGradient>0</ThermalConductivityGradient>
  <SpecificHeat>500</SpecificHeat>
  <SpecificHeatGradient>0</SpecificHeatGradient>
  <UseCustomThermalConductivity>>false</UseCustomThermalConductivity>
  <UseCustomSpecificHeat>>false</UseCustomSpecificHeat>
  <UseCustomDensity>>false</UseCustomDensity>
</Thermophysical>
</Riser>
  <RiserFrictionCoefficient>NaN</RiserFrictionCoefficient>
  <RiserRollerFrictionCoefficient>NaN</RiserRollerFrictionCoefficient>
- <WellboreSection>
  <HangerDepth>0</HangerDepth>
  <SettingDepth>2284.476</SettingDepth>
  <HoleDiameter>NaN</HoleDiameter>
  <TopOfCement>3335.1216</TopOfCement>
- <MaterialAboveCement xs:type="Fluid">
  <Name>Default</Name>
  <Description />
  <Density>1000</Density>
  <ReferenceTemperature>288.71</ReferenceTemperature>
  <BaseOilDensity>850</BaseOilDensity>
  <WaterDensity>1000</WaterDensity>
  <SolidsDensity>4200</SolidsDensity>

```

```

<FluidType>Liquid</FluidType>
<FoamQuality>NaN</FoamQuality>
<Glycol>NaN</Glycol>
<WaterPhaseSalinity>0</WaterPhaseSalinity>
- <ThermophysicalProperties xs:type="ThermophysicalFluid">
  <Density>1000</Density>
  <DensityGradient>NaN</DensityGradient>
  <ThermalConductivity>1</ThermalConductivity>
  <ThermalConductivityGradient>NaN</ThermalConductivityGradient>
  <SpecificHeat>4200</SpecificHeat>
  <SpecificHeatGradient>NaN</SpecificHeatGradient>
  <UseCustomThermalConductivity>false</UseCustomThermalConductivity>
  <UseCustomSpecificHeat>false</UseCustomSpecificHeat>
  <UseCustomDensity>false</UseCustomDensity>
  <StaticViscosity>0.02</StaticViscosity>
  <StaticViscosityGradient>NaN</StaticViscosityGradient>
  <UseCustomStaticViscosity>false</UseCustomStaticViscosity>
</ThermophysicalProperties>
- <Pvt>
  <FluidDensityTable xs:type="PtTable" />
  <SolubilityTable xs:type="PtTable" />
  <OilDensityTable xs:type="PtTable" />
- <Composition>
  <BaseOilType>Low toxicity</BaseOilType>
  <InfluxType>Dry gas</InfluxType>
  - <TemperatureRange>
    <Min>NaN</Min>
    <Max>NaN</Max>
    <Steps>0</Steps>
  </TemperatureRange>
  - <PressureRange>
    <Min>NaN</Min>
    <Max>NaN</Max>
    <Steps>0</Steps>
  </PressureRange>
  - <BaseOilComposition>
    <C8>NaN</C8>
    <C9>NaN</C9>
    <C10>NaN</C10>
    <C11>NaN</C11>
    <C12>NaN</C12>
    <C13>NaN</C13>
    <C14>NaN</C14>
    <C15>NaN</C15>
    <C16>NaN</C16>
    <C17>NaN</C17>
    <C18>NaN</C18>
    <C19>NaN</C19>
    <C20P>NaN</C20P>
  </BaseOilComposition>
  - <InfluxComposition>
    <N2>NaN</N2>
    <CO2>NaN</CO2>
    <H2S>NaN</H2S>
    <C1>NaN</C1>
    <C2>NaN</C2>
    <C3>NaN</C3>
    <NC4>NaN</NC4>

```



```

    <IC4>NaN</IC4>
    <NC5>NaN</NC5>
    <IC5>NaN</IC5>
    <C6>NaN</C6>
    <C7>NaN</C7>
    <C8>NaN</C8>
    <C9>NaN</C9>
    <C10>NaN</C10>
    <C11>NaN</C11>
    <C12>NaN</C12>
    <C13>NaN</C13>
    <C14>NaN</C14>
    <C15>NaN</C15>
    <C16>NaN</C16>
    <C17>NaN</C17>
    <C18>NaN</C18>
    <C19>NaN</C19>
    <C20P>NaN</C20P>
  </InfluxComposition>
</Composition>
- <SaturatedOilDensityTable>
  <DensitySlope>NaN</DensitySlope>
</SaturatedOilDensityTable>
</Pvt>
- <Rheology>
  <PlasticViscosity>NaN</PlasticViscosity>
  <YieldPoint>NaN</YieldPoint>
  <FannAt3Rpm>NaN</FannAt3Rpm>
  <RheologyType>Non-Newtonian; Fann tables</RheologyType>
</Rheology>
- <Brine>
  <NaCl>NaN</NaCl>
  <NaBr>NaN</NaBr>
  <KCl>NaN</KCl>
  <KBr>NaN</KBr>
  <CaCl2>NaN</CaCl2>
  <CaBr2>NaN</CaBr2>
  <ZnCl2>NaN</ZnCl2>
  <ZnBr2>NaN</ZnBr2>
</Brine>
- <OilWaterRatio>
  <OilPercent>0</OilPercent>
  <WaterPercent>100</WaterPercent>
</OilWaterRatio>
  <Viscosity>0.007</Viscosity>
  <GelProperties />
</MaterialAboveCement>
<FrictionCoefficient>NaN</FrictionCoefficient>
<RollerFrictionCoefficient>NaN</RollerFrictionCoefficient>
- <WellboreComponent xs:type="Casing">
  <Name>9.875</Name>
  <Description />
  <InnerDiameter>0.224409</InnerDiameter>
  <OuterDiameter>0.250825</OuterDiameter>
  <Length>NaN</Length>
  <EffectiveDiameter>NaN</EffectiveDiameter>
  <WeightPerLength>NaN</WeightPerLength>
  <Emodulus>210000000000</Emodulus>

```



```

    <YieldStrength>NaN</YieldStrength>
    <YieldStress>482700000</YieldStress>
  - <Thermophysical>
    <Density>7840</Density>
    <DensityGradient>NaN</DensityGradient>
    <ThermalConductivity>48</ThermalConductivity>
    <ThermalConductivityGradient>NaN</ThermalConductivityGradient>
    <SpecificHeat>500</SpecificHeat>
    <SpecificHeatGradient>NaN</SpecificHeatGradient>
    <UseCustomThermalConductivity>false</UseCustomThermalConductivity>
    <UseCustomSpecificHeat>false</UseCustomSpecificHeat>
    <UseCustomDensity>false</UseCustomDensity>
  </Thermophysical>
</WellboreComponent>
</WellboreSection>
- <OpenHoleSection>
  <Name>Open hole</Name>
  <Description />
  <InnerDiameter>0.1547876</InnerDiameter>
  <Length>1799.2344</Length>
  <FrictionCoefficient>NaN</FrictionCoefficient>
  <RollerFrictionCoefficient>NaN</RollerFrictionCoefficient>
</OpenHoleSection>
- <Divertor>
  <Name />
  <Description />
  <InnerDiameter>NaN</InnerDiameter>
  <Length>NaN</Length>
</Divertor>
</WellboreGeometry>
</Well>
- <Geology>
  <SurfaceTemperature>277.59444444444444</SurfaceTemperature>
  <LayerDepthReference>MD</LayerDepthReference>
  <AverageGeothermalGradient>0.03</AverageGeothermalGradient>
  - <Cuttings>
    <MaxConcentration>0.1</MaxConcentration>
    <MinRelativeVelocity>0.5</MinRelativeVelocity>
    <HoleCleaningCriterion>MaxConcentration</HoleCleaningCriterion>
    <Diameter>NaN</Diameter>
    <CuttingsMode>No slip</CuttingsMode>
  </Cuttings>
  - <Layer>
    <Top>3984.9552</Top>
    <Bottom>3992.2704</Bottom>
  - <Formation>
    <Name>18360 Sand</Name>
    <Description />
    <GeothermalGradient>NaN</GeothermalGradient>
  - <Thermophysical>
    <Density>NaN</Density>
    <DensityGradient>NaN</DensityGradient>
    <ThermalConductivity>NaN</ThermalConductivity>
    <ThermalConductivityGradient>NaN</ThermalConductivityGradient>
    <SpecificHeat>NaN</SpecificHeat>
    <SpecificHeatGradient>NaN</SpecificHeatGradient>
    <UseCustomThermalConductivity>false</UseCustomThermalConductivity>
    <UseCustomSpecificHeat>false</UseCustomSpecificHeat>
  </Thermophysical>
</Formation>
</Layer>
</Geology>

```

```

    <UseCustomDensity>false</UseCustomDensity>
  </Thermophysical>
- <Rock>
  <Permeability>NaN</Permeability>
  <Porosity>NaN</Porosity>
  <RockStrength>Hard</RockStrength>
  <Density>NaN</Density>
</Rock>
</Formation>
- <Reservoir>
  <Flowmodel>Linear PI</Flowmodel>
  <InfluxType>Black oil</InfluxType>
  <FlowValue>1.334442e-08</FlowValue>
  <Duration>NaN</Duration>
  <Volume>NaN</Volume>
  <ReservoirType>Undefined</ReservoirType>
  <InfluxIsGas>false</InfluxIsGas>
  <Temperature>399.8166666666667</Temperature>
  <Pressure>70705733.035</Pressure>
- <Water>
  <Density>1010</Density>
  <Viscosity>0.001</Viscosity>
  <Compressibility>1.1e-11</Compressibility>
  <VolumeFactor>1</VolumeFactor>
  <MassFraction>NaN</MassFraction>
  <WaterCut>0.1</WaterCut>
</Water>
- <Oil>
  <Density>895</Density>
  <Viscosity>0.002</Viscosity>
  <Compressibility>2e-10</Compressibility>
  <VolumeFactor>1.1</VolumeFactor>
  <MassFraction>NaN</MassFraction>
  <Gor>534.3228</Gor>
</Oil>
- <Gas>
  <Density>0.7167</Density>
  <N2>0</N2>
  <CO2>0</CO2>
  <H2S>0</H2S>
  <Hydrocarbon>1</Hydrocarbon>
  <MassFraction>NaN</MassFraction>
</Gas>
  <Injectivity>NaN</Injectivity>
- <A>
  <Injectivity>NaN</Injectivity>
  <Productivity>NaN</Productivity>
</A>
- <B>
  <Injectivity>NaN</Injectivity>
  <Productivity>NaN</Productivity>
</B>
- <C>
  <Injectivity>NaN</Injectivity>
  <Productivity>NaN</Productivity>
</C>
  <UseReservoirProperties>true</UseReservoirProperties>
</Reservoir>

```

```

</Layer>
- <PorePressure>
  <DepthReference>MD</DepthReference>
</PorePressure>
- <FracturePressure>
  <DepthReference>MD</DepthReference>
  <ReturnedAmount>0.5</ReturnedAmount>
  <SecondaryInitiationFactor>0</SecondaryInitiationFactor>
- <FracturePressurePoint>
  <Depth>1894.9416</Depth>
  <Pressure>21339954.85192616</Pressure>
  <ClosingPressure>NaN</ClosingPressure>
  <InitiationPressure>NaN</InitiationPressure>
</FracturePressurePoint>
- <FracturePressurePoint>
  <Depth>2434.1328</Depth>
  <Pressure>30420925.99753728</Pressure>
  <ClosingPressure>NaN</ClosingPressure>
  <InitiationPressure>NaN</InitiationPressure>
</FracturePressurePoint>
- <FracturePressurePoint>
  <Depth>2734.6656</Depth>
  <Pressure>37956291.48103373</Pressure>
  <ClosingPressure>NaN</ClosingPressure>
  <InitiationPressure>NaN</InitiationPressure>
</FracturePressurePoint>
- <FracturePressurePoint>
  <Depth>3525.012</Depth>
  <Pressure>53328948.3898032</Pressure>
  <ClosingPressure>NaN</ClosingPressure>
  <InitiationPressure>NaN</InitiationPressure>
</FracturePressurePoint>
- <FracturePressurePoint>
  <Depth>4008.12</Depth>
  <Pressure>70279219.114848</Pressure>
  <ClosingPressure>NaN</ClosingPressure>
  <InitiationPressure>NaN</InitiationPressure>
</FracturePressurePoint>
- <FracturePressurePoint>
  <Depth>4603.3944</Depth>
  <Pressure>80052705.51184627</Pressure>
  <ClosingPressure>NaN</ClosingPressure>
  <InitiationPressure>NaN</InitiationPressure>
</FracturePressurePoint>
- <FracturePressurePoint>
  <Depth>5596.128000000001</Depth>
  <Pressure>106632324.5782656</Pressure>
  <ClosingPressure>NaN</ClosingPressure>
  <InitiationPressure>NaN</InitiationPressure>
</FracturePressurePoint>
</FracturePressure>
<SeaBedTemperature>277.0388888888889</SeaBedTemperature>
</Geology>
- <SurfaceEquipment>
  <UseRch>false</UseRch>
- <Chokeline>
  <Name />
  <Description />

```

```

    <InnerDiameter>NaN</InnerDiameter>
    <Length>NaN</Length>
    <LineCount>1</LineCount>
  - <Choke>
    <PressureAfter>NaN</PressureAfter>
    <ClosureTime>1</ClosureTime>
    <ChokeControl>Opening</ChokeControl>
    <PressureChange>10000</PressureChange>
    <ConstantBottomHoleEcd>NaN</ConstantBottomHoleEcd>
    <ProportionalGain>NaN</ProportionalGain>
    <FeedForwardGain>NaN</FeedForwardGain>
    <IntegralGain>NaN</IntegralGain>
    <DerivativeGain>NaN</DerivativeGain>
  </Choke>
</Chokeline>
- <SurfacePipeline>
  <Name />
  <Description />
  <InnerDiameter>NaN</InnerDiameter>
  <Length>NaN</Length>
  <BendCount>0</BendCount>
</SurfacePipeline>
- <Pump>
  <VolumetricOutput>0.001</VolumetricOutput>
  <LiquidRateChange>0.0008412024000000001</LiquidRateChange>
  <ResponseDelay>NaN</ResponseDelay>
  <GasRateChange>NaN</GasRateChange>
  <CirculationPressure>NaN</CirculationPressure>
</Pump>
- <Bop>
  <ResponseDelay>NaN</ResponseDelay>
  <ClosureTime>1</ClosureTime>
</Bop>
- <Separator>
  <Height>NaN</Height>
  <Diameter>NaN</Diameter>
  <Level>NaN</Level>
  <WorkingPressure>NaN</WorkingPressure>
- <FlareLine>
  <Name />
  <Description />
  <InnerDiameter>NaN</InnerDiameter>
  <Length>NaN</Length>
</FlareLine>
- <PitLine>
  <Name />
  <Description />
  <InnerDiameter>NaN</InnerDiameter>
  <Length>NaN</Length>
  <Level>NaN</Level>
</PitLine>
</Separator>
- <ReturnLine>
  <Name />
  <Description />
  <InnerDiameter>0.3048</InnerDiameter>
  <Length>21.336</Length>
</ReturnLine>

```

```

    <AnnulusSurfacePressure>15478729.465</AnnulusSurfacePressure>
  </SurfaceEquipment>
- <TemperatureProperties>
  <TemperatureModel>Holmes and Swift</TemperatureModel>
  <InitialTemperatureSource>Gradient</InitialTemperatureSource>
  <DrillstringTemperature />
  <AnnulusTemperature />
- <FluidSurfaceTemperature>
  <Injection>283.15</Injection>
  <AnnulusOutlet>NaN</AnnulusOutlet>
  <ChokelineOutlet>NaN</ChokelineOutlet>
  <Difference>NaN</Difference>
  <InjectionTemperatureModel>ConstantInjection</InjectionTemperatureModel>
- <PitTank>
  <Volume>NaN</Volume>
  <InitialTemperature>283.15</InitialTemperature>
</PitTank>
</FluidSurfaceTemperature>
- <HeatTransferCoefficient>
  <AcrossDrillpipe>170</AcrossDrillpipe>
  <AcrossWellbore>5.6</AcrossWellbore>
</HeatTransferCoefficient>
- <InjectionLineTemperature>
  <InletTemperature>263</InletTemperature>
</InjectionLineTemperature>
</TemperatureProperties>
- <Operation>
  <GridCellCount>90</GridCellCount>
- <StartupConditions>
  <BitDepth>2284.476</BitDepth>
  <UseDrillstring>false</UseDrillstring>
  <UseSeparator>false</UseSeparator>
  <UseRiserCalculation>false</UseRiserCalculation>
  <UseHydrateCalculation>false</UseHydrateCalculation>
  <TargetDepth>NaN</TargetDepth>
  <InitialFluid>BP</InitialFluid>
</StartupConditions>
- <WellControl>
- <Simple>
  - <PitAlarm>
    <Value>NaN</Value>
    - <Range>
      <Min>NaN</Min>
      <Max>NaN</Max>
      <Steps>0</Steps>
    </Range>
  </PitAlarm>
  <FlowCheckType>No flow check</FlowCheckType>
  <FlowCheckTime>NaN</FlowCheckTime>
  <FlowCheckVolume>NaN</FlowCheckVolume>
  <ShutInPeriodType>Until influx stopped</ShutInPeriodType>
  <ShutInPeriod>NaN</ShutInPeriod>
  <CirculationMode>Manual</CirculationMode>
- <CirculationRate>
  <Value>NaN</Value>
  - <Range>
    <Min>NaN</Min>
    <Max>NaN</Max>

```

```

    <Steps>0</Steps>
  </Range>
</CirculationRate>
<DynamicSafetyMargin>NaN</DynamicSafetyMargin>
<StaticSafetyMargin>NaN</StaticSafetyMargin>
<KillMudRate>NaN</KillMudRate>
<ReferenceDepth>NaN</ReferenceDepth>
<ReferencePressure>NaN</ReferencePressure>
- <KickIntensity>
  <Value>NaN</Value>
  - <Range>
    <Min>NaN</Min>
    <Max>NaN</Max>
    <Steps>0</Steps>
  </Range>
</KickIntensity>
<DegasserCapacity>NaN</DegasserCapacity>
<KillMudDensity>NaN</KillMudDensity>
- <PreCirculation>
  - <RateItem>
    <Duration>3600</Duration>
    <Rate>NaN</Rate>
  </RateItem>
</PreCirculation>
</Simple>
- <KickTolerance>
  - <PitAlarm>
    <Value>NaN</Value>
    - <Range>
      <Min>NaN</Min>
      <Max>NaN</Max>
      <Steps>0</Steps>
    </Range>
  </PitAlarm>
  <FlowCheckType>No flow check</FlowCheckType>
  <FlowCheckTime>NaN</FlowCheckTime>
  <FlowCheckVolume>NaN</FlowCheckVolume>
  <ShutInPeriodType>Until influx stopped</ShutInPeriodType>
  <ShutInPeriod>NaN</ShutInPeriod>
  <CirculationMode>Manual</CirculationMode>
- <CirculationRate>
  <Value>NaN</Value>
  - <Range>
    <Min>NaN</Min>
    <Max>NaN</Max>
    <Steps>0</Steps>
  </Range>
</CirculationRate>
<DynamicSafetyMargin>NaN</DynamicSafetyMargin>
<StaticSafetyMargin>NaN</StaticSafetyMargin>
<KillMudRate>NaN</KillMudRate>
<ReferenceDepth>NaN</ReferenceDepth>
<ReferencePressure>NaN</ReferencePressure>
- <KickIntensity>
  <Value>NaN</Value>
  - <Range>
    <Min>NaN</Min>
    <Max>NaN</Max>

```

```

    <Steps>0</Steps>
  </Range>
  </KickIntensity>
  <DegasserCapacity>NaN</DegasserCapacity>
  <KillMudDensity>NaN</KillMudDensity>
  <PreCirculation />
  </KickTolerance>
  <KickToleranceMode>Max kick size</KickToleranceMode>
  <WellControlBatch />
</WellControl>
- <Control>
- <ControlParameter>
  <Parameter>PumpedFluid</Parameter>
  <Name>BP</Name>
</ControlParameter>
- <ControlParameter>
  <Parameter>LiquidPumpOn</Parameter>
  <Value>0</Value>
</ControlParameter>
- <ControlParameter>
  <Parameter>ParasitePumpedFluid</Parameter>
  <Name>Bob Grace</Name>
</ControlParameter>
- <ControlParameter>
  <Parameter>ParasiteLiquidPumpOn</Parameter>
  <Value>1</Value>
</ControlParameter>
- <ControlParameter>
  <Parameter>ParasiteLiquidPumpRate</Parameter>
  <Value>0.03974685</Value>
</ControlParameter>
- <ControlParameter>
  <Parameter>Rop</Parameter>
  <Value>NaN</Value>
</ControlParameter>
</Control>
<PvtFilename>Black oil.tab</PvtFilename>
<MaxSurveyPoints>2</MaxSurveyPoints>
</Operation>
- <FluidCollection>
- <FluidSection>
  - <FluidModels>
    <PvtModel>Black oil</PvtModel>
    <OilDensityModel>Glasso</OilDensityModel>
    <WaterDensityModel>Dodson-Standing</WaterDensityModel>
    <RheologyModel>Robertson-Stiff</RheologyModel>
  </FluidModels>
  - <Fluid>
    <Name>BP</Name>
    <Description />
    <Density>1198.264</Density>
    <ReferenceTemperature>288.71</ReferenceTemperature>
    <BaseOilDensity>850</BaseOilDensity>
    <WaterDensity>1000</WaterDensity>
    <SolidsDensity>4200</SolidsDensity>
    <FluidType>Liquid</FluidType>
    <FoamQuality>NaN</FoamQuality>
    <Glycol>NaN</Glycol>
  </Fluid>
</FluidSection>
</FluidCollection>

```



```

    <WaterPhaseSalinity>0</WaterPhaseSalinity>
  - <ThermophysicalProperties xs:type="ThermophysicalFluid">
    <Density>1198.264</Density>
    <DensityGradient>NaN</DensityGradient>
    <ThermalConductivity>0.4250236097459533</ThermalConductivity>
    <ThermalConductivityGradient>NaN</ThermalConductivityGradient>
    <SpecificHeat>1855.59599674678</SpecificHeat>
    <SpecificHeatGradient>NaN</SpecificHeatGradient>
    <UseCustomThermalConductivity>>false</UseCustomThermalConductivity>
    <UseCustomSpecificHeat>>false</UseCustomSpecificHeat>
    <UseCustomDensity>>false</UseCustomDensity>
    <StaticViscosity>0.02</StaticViscosity>
    <StaticViscosityGradient>NaN</StaticViscosityGradient>
    <UseCustomStaticViscosity>>false</UseCustomStaticViscosity>
  </ThermophysicalProperties>
  - <Pvt>
    <FluidDensityTable xs:type="PtTable" />
    <SolubilityTable xs:type="PtTable" />
    <OilDensityTable xs:type="PtTable" />
  - <Composition>
    <BaseOilType>Low toxicity</BaseOilType>
    <InfluxType>Dry gas</InfluxType>
    - <TemperatureRange>
      <Min>NaN</Min>
      <Max>NaN</Max>
      <Steps>0</Steps>
    </TemperatureRange>
    - <PressureRange>
      <Min>NaN</Min>
      <Max>NaN</Max>
      <Steps>0</Steps>
    </PressureRange>
    - <BaseOilComposition>
      <C8>0</C8>
      <C9>0</C9>
      <C10>0</C10>
      <C11>0</C11>
      <C12>0</C12>
      <C13>0</C13>
      <C14>0.012</C14>
      <C15>0</C15>
      <C16>0.583</C16>
      <C17>0</C17>
      <C18>0.337</C18>
      <C19>0</C19>
      <C20P>0.068</C20P>
    </BaseOilComposition>
    - <InfluxComposition>
      <N2>0</N2>
      <CO2>0</CO2>
      <H2S>0</H2S>
      <C1>0.96</C1>
      <C2>0.036</C2>
      <C3>0</C3>
      <NC4>0</NC4>
      <IC4>0</IC4>
      <NC5>0</NC5>
      <IC5>0</IC5>

```

```

    <C6>0</C6>
    <C7>0</C7>
    <C8>0</C8>
    <C9>0</C9>
    <C10>0</C10>
    <C11>0</C11>
    <C12>0</C12>
    <C13>0</C13>
    <C14>0</C14>
    <C15>0</C15>
    <C16>0</C16>
    <C17>0.004</C17>
    <C18>0</C18>
    <C19>0</C19>
    <C20P>0</C20P>
  </InfluxComposition>
</Composition>
- <SaturatedOilDensityTable>
  <DensitySlope>NaN</DensitySlope>
</SaturatedOilDensityTable>
</Pvt>
- <Rheology>
  <PlasticViscosity>NaN</PlasticViscosity>
  <YieldPoint>NaN</YieldPoint>
  <FannAt3Rpm>NaN</FannAt3Rpm>
  <RheologyType>Newtonian</RheologyType>
- <RheologySection>
  <Pressure>101325</Pressure>
  <Temperature>323.15</Temperature>
</RheologySection>
</Rheology>
- <Brine>
  <NaCl>NaN</NaCl>
  <NaBr>NaN</NaBr>
  <KCl>NaN</KCl>
  <KBr>NaN</KBr>
  <CaCl2>NaN</CaCl2>
  <CaBr2>NaN</CaBr2>
  <ZnCl2>NaN</ZnCl2>
  <ZnBr2>NaN</ZnBr2>
</Brine>
- <OilWaterRatio>
  <OilPercent>80</OilPercent>
  <WaterPercent>20</WaterPercent>
</OilWaterRatio>
  <Viscosity>0.003</Viscosity>
  <GelProperties />
</Fluid>
</FluidSection>
- <FluidSection>
- <FluidModels>
  <PvtModel>Black oil</PvtModel>
  <OilDensityModel>Glasso</OilDensityModel>
  <WaterDensityModel>Dodson-Standing</WaterDensityModel>
  <RheologyModel>Robertson-Stiff</RheologyModel>
</FluidModels>
- <Fluid>
  <Name>BP Kill Fluid</Name>

```

```

<Description />
<Density>1917.2224</Density>
<ReferenceTemperature>288.71</ReferenceTemperature>
<BaseOilDensity>850</BaseOilDensity>
<WaterDensity>1000</WaterDensity>
<SolidsDensity>4200</SolidsDensity>
<FluidType>Liquid</FluidType>
<FoamQuality>NaN</FoamQuality>
<Glycol>NaN</Glycol>
<WaterPhaseSalinity>0</WaterPhaseSalinity>
- <ThermophysicalProperties xs:type="ThermophysicalFluid">
  <Density>1917.2224</Density>
  <DensityGradient>NaN</DensityGradient>
  <ThermalConductivity>0.9671251752044083</ThermalConductivity>
  <ThermalConductivityGradient>NaN</ThermalConductivityGradient>
  <SpecificHeat>1123.331835316135</SpecificHeat>
  <SpecificHeatGradient>NaN</SpecificHeatGradient>
  <UseCustomThermalConductivity>>false</UseCustomThermalConductivity>
  <UseCustomSpecificHeat>>false</UseCustomSpecificHeat>
  <UseCustomDensity>>false</UseCustomDensity>
  <StaticViscosity>0.02</StaticViscosity>
  <StaticViscosityGradient>NaN</StaticViscosityGradient>
  <UseCustomStaticViscosity>>false</UseCustomStaticViscosity>
</ThermophysicalProperties>
- <Pvt>
  <FluidDensityTable xs:type="PtTable" />
  <SolubilityTable xs:type="PtTable" />
  <OilDensityTable xs:type="PtTable" />
- <Composition>
  <BaseOilType>Low toxicity</BaseOilType>
  <InfluxType>Dry gas</InfluxType>
- <TemperatureRange>
  <Min>NaN</Min>
  <Max>NaN</Max>
  <Steps>0</Steps>
</TemperatureRange>
- <PressureRange>
  <Min>NaN</Min>
  <Max>NaN</Max>
  <Steps>0</Steps>
</PressureRange>
- <BaseOilComposition>
  <C8>0</C8>
  <C9>0</C9>
  <C10>0</C10>
  <C11>0</C11>
  <C12>0</C12>
  <C13>0</C13>
  <C14>0.012</C14>
  <C15>0</C15>
  <C16>0.583</C16>
  <C17>0</C17>
  <C18>0.337</C18>
  <C19>0</C19>
  <C20P>0.068</C20P>
</BaseOilComposition>
- <InfluxComposition>
  <N2>0</N2>

```

```

    <CO2>0</CO2>
    <H2S>0</H2S>
    <C1>0.96</C1>
    <C2>0.036</C2>
    <C3>0</C3>
    <NC4>0</NC4>
    <IC4>0</IC4>
    <NC5>0</NC5>
    <IC5>0</IC5>
    <C6>0</C6>
    <C7>0</C7>
    <C8>0</C8>
    <C9>0</C9>
    <C10>0</C10>
    <C11>0</C11>
    <C12>0</C12>
    <C13>0</C13>
    <C14>0</C14>
    <C15>0</C15>
    <C16>0</C16>
    <C17>0.004</C17>
    <C18>0</C18>
    <C19>0</C19>
    <C20P>0</C20P>
  </InfluxComposition>
</Composition>
- <SaturatedOilDensityTable>
  <DensitySlope>NaN</DensitySlope>
</SaturatedOilDensityTable>
</Pvt>
- <Rheology>
  <PlasticViscosity>NaN</PlasticViscosity>
  <YieldPoint>NaN</YieldPoint>
  <FannAt3Rpm>NaN</FannAt3Rpm>
  <RheologyType>Newtonian</RheologyType>
- <RheologySection>
  <Pressure>101325</Pressure>
  <Temperature>323.15</Temperature>
</RheologySection>
</Rheology>
- <Brine>
  <NaCl>NaN</NaCl>
  <NaBr>NaN</NaBr>
  <KCl>NaN</KCl>
  <KBr>NaN</KBr>
  <CaCl2>NaN</CaCl2>
  <CaBr2>NaN</CaBr2>
  <ZnCl2>NaN</ZnCl2>
  <ZnBr2>NaN</ZnBr2>
</Brine>
- <OilWaterRatio>
  <OilPercent>80</OilPercent>
  <WaterPercent>20</WaterPercent>
</OilWaterRatio>
  <Viscosity>0.03</Viscosity>
  <GelProperties />
</Fluid>
</FluidSection>

```

```

- <FluidSection>
- <FluidModels>
  <PvtModel>Black oil</PvtModel>
  <OilDensityModel>Glasso</OilDensityModel>
  <WaterDensityModel>Dodson-Standing</WaterDensityModel>
  <RheologyModel>Robertson-Stiff</RheologyModel>
</FluidModels>
- <Fluid>
  <Name>Bob Grace</Name>
  <Description />
  <Density>2396.528</Density>
  <ReferenceTemperature>288.71</ReferenceTemperature>
  <BaseOilDensity>850</BaseOilDensity>
  <WaterDensity>1000</WaterDensity>
  <SolidsDensity>4200</SolidsDensity>
  <FluidType>Liquid</FluidType>
  <FoamQuality>NaN</FoamQuality>
  <Glycol>NaN</Glycol>
  <WaterPhaseSalinity>0</WaterPhaseSalinity>
- <ThermophysicalProperties xs:type="ThermophysicalFluid">
  <Density>2396.528</Density>
  <DensityGradient>NaN</DensityGradient>
  <ThermalConductivity>1.35208402250197</ThermalConductivity>
  <ThermalConductivityGradient>NaN</ThermalConductivityGradient>
  <SpecificHeat>879.24378150592</SpecificHeat>
  <SpecificHeatGradient>NaN</SpecificHeatGradient>
  <UseCustomThermalConductivity>false</UseCustomThermalConductivity>
  <UseCustomSpecificHeat>false</UseCustomSpecificHeat>
  <UseCustomDensity>false</UseCustomDensity>
  <StaticViscosity>0.02</StaticViscosity>
  <StaticViscosityGradient>NaN</StaticViscosityGradient>
  <UseCustomStaticViscosity>false</UseCustomStaticViscosity>
</ThermophysicalProperties>
- <Pvt>
  <FluidDensityTable xs:type="PtTable" />
  <SolubilityTable xs:type="PtTable" />
  <OilDensityTable xs:type="PtTable" />
- <Composition>
  <BaseOilType>Low toxicity</BaseOilType>
  <InfluxType>Dry gas</InfluxType>
- <TemperatureRange>
  <Min>NaN</Min>
  <Max>NaN</Max>
  <Steps>0</Steps>
</TemperatureRange>
- <PressureRange>
  <Min>NaN</Min>
  <Max>NaN</Max>
  <Steps>0</Steps>
</PressureRange>
- <BaseOilComposition>
  <C8>0</C8>
  <C9>0</C9>
  <C10>0</C10>
  <C11>0</C11>
  <C12>0</C12>
  <C13>0</C13>
  <C14>0.012</C14>

```

```

    <C15>0</C15>
    <C16>0.583</C16>
    <C17>0</C17>
    <C18>0.337</C18>
    <C19>0</C19>
    <C20P>0.068</C20P>
  </BaseOilComposition>
- <InfluxComposition>
  <N2>0</N2>
  <CO2>0</CO2>
  <H2S>0</H2S>
  <C1>0.96</C1>
  <C2>0.036</C2>
  <C3>0</C3>
  <NC4>0</NC4>
  <IC4>0</IC4>
  <NC5>0</NC5>
  <IC5>0</IC5>
  <C6>0</C6>
  <C7>0</C7>
  <C8>0</C8>
  <C9>0</C9>
  <C10>0</C10>
  <C11>0</C11>
  <C12>0</C12>
  <C13>0</C13>
  <C14>0</C14>
  <C15>0</C15>
  <C16>0</C16>
  <C17>0.004</C17>
  <C18>0</C18>
  <C19>0</C19>
  <C20P>0</C20P>
</InfluxComposition>
</Composition>
- <SaturatedOilDensityTable>
  <DensitySlope>NaN</DensitySlope>
</SaturatedOilDensityTable>
</Pvt>
- <Rheology>
  <PlasticViscosity>NaN</PlasticViscosity>
  <YieldPoint>NaN</YieldPoint>
  <FannAt3Rpm>NaN</FannAt3Rpm>
  <RheologyType>Newtonian</RheologyType>
- <RheologySection>
  <Pressure>101325</Pressure>
  <Temperature>323.15</Temperature>
</RheologySection>
</Rheology>
- <Brine>
  <NaCl>NaN</NaCl>
  <NaBr>NaN</NaBr>
  <KCl>NaN</KCl>
  <KBr>NaN</KBr>
  <CaCl2>NaN</CaCl2>
  <CaBr2>NaN</CaBr2>
  <ZnCl2>NaN</ZnCl2>
  <ZnBr2>NaN</ZnBr2>

```

```

    </Brine>
  - <OilWaterRatio>
    <OilPercent>80</OilPercent>
    <WaterPercent>20</WaterPercent>
  </OilWaterRatio>
  <Viscosity>0.065</Viscosity>
  <GelProperties />
</Fluid>
</FluidSection>
- <SubModels>
  <PressureLossModel>Semi-empirical</PressureLossModel>
  <GasDensityModel>Hall-Yarborough</GasDensityModel>
  <FrictionFactorModel>Ed. Technip 1982</FrictionFactorModel>
- <FluidModels>
  <PvtModel>Black oil</PvtModel>
  <OilDensityModel>Glasso</OilDensityModel>
  <WaterDensityModel>Dodson-Standing</WaterDensityModel>
  <RheologyModel>Robertson-Stiff</RheologyModel>
</FluidModels>
<Gelling>false</Gelling>
</SubModels>
</FluidCollection>
- <ApplicationData>
  - <AbcData xs:type="DrillbenchData">
    <Name>OLGA ABC</Name>
    <PlotLayout>Custom plots 3 Ver 0.294352 Hor 0.5 Plot LiquidFlowrateOut
    (ChartDef object TUnitChart Left = 0 Top = 0 Width = 236 Height = 192 XUnits
    = OptionDialog.TimeUnits YUnits = OptionDialog.LiquidRateUnits XTitle =
    'Time' YTitle = 'Flowrate' HorizAxis = aBottomAxis Logo = logoOlga Align =
    alClient AllowPanning = pmNone BackColor = clWindow BackWall.Color =
    clWindow BevelOuter = bvNone BorderStyle = bsSingle BottomAxis.Axis.Width
    = 1 BottomAxis.Grid.Color = clSilver BottomAxis.LabelsSeparation = 30
    BottomAxis.MinorTickCount = 4 BottomAxis.Title.Caption = 'Time (min)' Color
    = clWindow DepthAxis.Axis.Width = 1 DepthAxis.Grid.Color = clSilver
    DepthAxis.LabelsSeparation = 50 LeftAxis.Axis.Width = 1 LeftAxis.Grid.Color =
    clSilver LeftAxis.LabelsSeparation = 50 LeftAxis.MaximumOffset = 5
    LeftAxis.MinimumOffset = 5 LeftAxis.MinorTickCount = 4 LeftAxis.Title.Caption
    = 'Flowrate (bbl/min)' Legend.Alignment = laBottom Legend.CheckBoxes =
    True Legend.Color = clWindow Legend.LegendStyle = lsSeries
    Legend.Shadow.HorizSize = 0 Legend.Shadow.VertSize = 0 Page = 1
    RightAxis.Axis.Width = 1 RightAxis.Grid.Color = clSilver
    RightAxis.LabelsSeparation = 50 RightAxis.MinorTickCount = 4 ScaleLastPage
    = True TabOrder = 0 Title.Font.Color = clBlack Title.Font.Style = [fsBold]
    Title.Text.Strings = ( 'Liquid flow rate out') TopAxis.Axis.Width = 1
    TopAxis.Grid.Color = clSilver TopAxis.LabelsSeparation = 30
    TopAxis.MinorTickCount = 4 View3D = False ExplicitWidth = 40 ExplicitHeight
    = 20 object CursorTool1: TCursorTool ShowInEditor = False Active = False
    Style = cssVertical end object AnnotationTool1: TAnnotationTool ShowInEditor
    = False Active = False Callout.Brush.Color = clBlack Callout.Arrow.Visible =
    False Shape.Font.Name = 'Arial Narrow' Shape.Shadow.HorizSize = 0
    Shape.Shadow.VertSize = 0 Shape.Text = 'X:'#39'#13'#39'Y:' Text =
    'X:'#39'#13'#39'Y:' end object TColorLineTool Tag = -1 Active = False
    AllowDrag = False Value = -1.0000000000000000 AxisID = 0 end end
    ChartDef) Plot GasFlowrateOut (ChartDef object TUnitChart Left = 0 Top = 0
    Width = 236 Height = 192 XUnits = OptionDialog.TimeUnits YUnits =
    OptionDialog.GasRateUnits XTitle = 'Time' YTitle = 'Flowrate' HorizAxis =
    aBottomAxis Logo = logoOlga Align = alClient AllowPanning = pmNone
    BackColor = clWindow BackWall.Color = clWindow BevelOuter = bvNone
    BorderStyle = bsSingle BottomAxis.Axis.Width = 1 BottomAxis.Grid.Color =
    clSilver BottomAxis.LabelsSeparation = 30 BottomAxis.MinorTickCount = 4
    BottomAxis.Title.Caption = 'Time (min)' Color = clWindow

```



```

DepthAxis.Axis.Width = 1 DepthAxis.Grid.Color = clSilver
DepthAxis.LabelsSeparation = 50 LeftAxis.Axis.Width = 1 LeftAxis.Grid.Color =
clSilver LeftAxis.LabelsSeparation = 50 LeftAxis.MaximumOffset = 5
LeftAxis.MinimumOffset = 5 LeftAxis.MinorTickCount = 4 LeftAxis.Title.Caption
= 'Flowrate (MMscf/day)' Legend.Alignment = laBottom Legend.CheckBoxes =
True Legend.Color = clWindow Legend.LegendStyle = lsSeries
Legend.Shadow.HorizSize = 0 Legend.Shadow.VertSize = 0 Page = 1
RightAxis.Axis.Width = 1 RightAxis.Grid.Color = clSilver
RightAxis.LabelsSeparation = 50 RightAxis.MinorTickCount = 4 ScaleLastPage
= True TabOrder = 0 Title.Font.Color = clBlack Title.Font.Style = [fsBold]
Title.Text.Strings = ( 'Gas flow rate out') TopAxis.Axis.Width = 1
TopAxis.Grid.Color = clSilver TopAxis.LabelsSeparation = 30
TopAxis.MinorTickCount = 4 View3D = False ExplicitWidth = 40 ExplicitHeight
= 364 object CursorTool1: TCursorTool ShowInEditor = False Active = False
Style = cssVertical end object AnnotationTool1: TAnnotationTool ShowInEditor
= False Active = False Callout.Brush.Color = clBlack Callout.Arrow.Visible =
False Shape.Font.Name = 'Arial Narrow' Shape.Shadow.HorizSize = 0
Shape.Shadow.VertSize = 0 Shape.Text = 'X:#39#13#39#39#Y:' Text =
'X:#39#13#39#39#Y:' end object TColorLineTool Tag = -1 Active = False
AllowDrag = False Value = -1.0000000000000000 AxisID = 0 end end
ChartDef) Ver 0.387887 Hor 0.50173 Plot BottomholePressure (ChartDef object
TUnitChart Left = 0 Top = 0 Width = 218 Height = 192 XUnits =
OptionDialog.TimeUnits YUnits = OptionDialog.PressureUnits XTitle = 'Time'
YTitle = 'Pressure' HorizAxis = aBottomAxis Logo = logoOlga Align = alClient
AllowPanning = pmNone BackColor = clWindow BackWall.Color = clWindow
BevelOuter = bvNone BorderStyle = bsSingle BottomAxis.Axis.Width = 1
BottomAxis.Grid.Color = clSilver BottomAxis.LabelsSeparation = 30
BottomAxis.MinorTickCount = 4 BottomAxis.Title.Caption = 'Time (min)' Color
= clWindow DepthAxis.Axis.Width = 1 DepthAxis.Grid.Color = clSilver
DepthAxis.LabelsSeparation = 50 LeftAxis.Automatic = False
LeftAxis.AutomaticMaximum = False LeftAxis.AutomaticMinimum = False
LeftAxis.Axis.Width = 1 LeftAxis.Grid.Color = clSilver LeftAxis.LabelsSeparation
= 50 LeftAxis.Maximum = 12000.0000000000000000000000000000
LeftAxis.MaximumOffset = 5 LeftAxis.Minimum = 8000.0000000000000000000000000000
LeftAxis.MinimumOffset = 5 LeftAxis.MinorTickCount = 4 LeftAxis.Title.Caption
= 'Pressure (psi)' Legend.Alignment = laBottom Legend.CheckBoxes = True
Legend.Color = clWindow Legend.LegendStyle = lsSeries
Legend.Shadow.HorizSize = 0 Legend.Shadow.VertSize = 0 Page = 1
RightAxis.Axis.Width = 1 RightAxis.Grid.Color = clSilver
RightAxis.LabelsSeparation = 50 RightAxis.MinorTickCount = 4 ScaleLastPage
= True TabOrder = 0 Title.Font.Color = clBlack Title.Font.Style = [fsBold]
Title.Text.Strings = ( 'Bottomhole pressure') TopAxis.Axis.Width = 1
TopAxis.Grid.Color = clSilver TopAxis.LabelsSeparation = 30
TopAxis.MinorTickCount = 4 View3D = False ExplicitWidth = 40 ExplicitHeight
= 20 object CursorTool1: TCursorTool ShowInEditor = False Active = False
Style = cssVertical end object AnnotationTool1: TAnnotationTool ShowInEditor
= False Active = False Callout.Brush.Color = clBlack Callout.Arrow.Visible =
False Shape.Font.Name = 'Arial Narrow' Shape.Shadow.HorizSize = 0
Shape.Shadow.VertSize = 0 Shape.Text = 'X:#39#13#39#39#Y:' Text =
'X:#39#13#39#39#Y:' end object TColorLineTool Tag = -1 Active = False
AllowDrag = False Value = -1.0000000000000000 AxisID = 0 end end
ChartDef) Plot InfluxGasMass (ChartDef object TUnitChart Left = 0 Top = 0
Width = 218 Height = 192 XUnits = OptionDialog.TimeUnits YUnits =
OptionDialog.MassRateUnits XTitle = 'Time' YTitle = 'Mass rate' HorizAxis =
aBottomAxis Logo = logoOlga Align = alClient AllowPanning = pmNone
BackColor = clWindow BackWall.Color = clWindow BevelOuter = bvNone
BorderStyle = bsSingle BottomAxis.Axis.Width = 1 BottomAxis.Grid.Color =
clSilver BottomAxis.LabelsSeparation = 30 BottomAxis.MinorTickCount = 4
BottomAxis.Title.Caption = 'Time (min)' Color = clWindow
DepthAxis.Axis.Width = 1 DepthAxis.Grid.Color = clSilver
DepthAxis.LabelsSeparation = 50 LeftAxis.Axis.Width = 1 LeftAxis.Grid.Color =
clSilver LeftAxis.LabelsSeparation = 50 LeftAxis.MaximumOffset = 5
LeftAxis.MinimumOffset = 5 LeftAxis.MinorTickCount = 4 LeftAxis.Title.Caption

```

```

= 'Mass rate (lbm/s)' Legend.Alignment = laBottom Legend.CheckBoxes = True
Legend.Color = clWindow Legend.LegendStyle = lsSeries
Legend.Shadow.HorizSize = 0 Legend.Shadow.VertSize = 0 Page = 1
RightAxis.Axis.Width = 1 RightAxis.Grid.Color = clSilver
RightAxis.LabelsSeparation = 50 RightAxis.MinorTickCount = 4 ScaleLastPage
= True TabOrder = 0 Title.Font.Color = clBlack Title.Font.Style = [fsBold]
Title.Text.Strings = ( 'Influx from reservoir (mass rate)') TopAxis.Axis.Width =
1 TopAxis.Grid.Color = clSilver TopAxis.LabelsSeparation = 30
TopAxis.MinorTickCount = 4 View3D = False ExplicitWidth = 40 ExplicitHeight
= 364 object CursorTool1: TCursorTool ShowInEditor = False Active = False
Style = cssVertical end object AnnotationTool1: TAnnotationTool ShowInEditor
= False Active = False Callout.Brush.Color = clBlack Callout.Arrow.Visible =
False Shape.Font.Name = 'Arial Narrow' Shape.Shadow.HorizSize = 0
Shape.Shadow.VertSize = 0 Shape.Text = 'X:#39'#13'#39'Y:' Text =
'X:#39'#13'#39'Y:' end object TColorLineTool Tag = -1 Active = False
AllowDrag = False Value = -1.0000000000000000 AxisID = 0 end end
ChartDef) Ver 0.5 Plot PressureProfile (ChartDef object TUnitChart Left = 0 Top
= 0 Width = 170 Height = 389 XUnits = OptionDialog.PressureUnits YUnits =
OptionDialog.LengthUnits XTitle = 'Pressure' YTitle = 'Depth' TrackerLayout =
dHorizontal Logo = logoOlga Align = alClient AllowPanning = pmNone
BackColor = clWindow BackWall.Color = clWindow BevelOuter = bvNone
BorderStyle = bsSingle BottomAxis.Axis.Width = 1 BottomAxis.Grid.Color =
clSilver BottomAxis.LabelsSeparation = 30 BottomAxis.MinorTickCount = 4
Color = clWindow DepthAxis.Axis.Width = 1 DepthAxis.Grid.Color = clSilver
DepthAxis.LabelsSeparation = 50 LeftAxis.Axis.Width = 1 LeftAxis.Grid.Color =
clSilver LeftAxis.Inverted = True LeftAxis.LabelsSeparation = 50
LeftAxis.MinorTickCount = 4 LeftAxis.Title.Caption = 'Depth (ft)'
Legend.Alignment = laBottom Legend.CheckBoxes = True Legend.Color =
clWindow Legend.LegendStyle = lsSeries Legend.Shadow.HorizSize = 0
Legend.Shadow.VertSize = 0 Page = 1 RightAxis.Axis.Width = 1
RightAxis.Grid.Color = clSilver RightAxis.LabelsSeparation = 50
RightAxis.MinorTickCount = 4 ScaleLastPage = True TabOrder = 0
Title.Font.Color = clBlack Title.Font.Style = [fsBold] Title.Text.Strings =
( 'Annulus and fracture presusre') TopAxis.Automatic = False
TopAxis.AutomaticMinimum = False TopAxis.Axis.Width = 1 TopAxis.Grid.Color
= clSilver TopAxis.LabelsSeparation = 30 TopAxis.MaximumOffset = 5
TopAxis.MinimumOffset = 5 TopAxis.MinorTickCount = 4 TopAxis.Title.Caption
= 'Pressure (psi)' View3D = False ExplicitWidth = 40 object CursorTool1:
TCursorTool ShowInEditor = False Active = False Style = cssHorizontal end
object AnnotationTool1: TAnnotationTool ShowInEditor = False Active = False
Callout.Brush.Color = clBlack Callout.Arrow.Visible = False Shape.Font.Name =
'Arial Narrow' Shape.Shadow.HorizSize = 0 Shape.Shadow.VertSize = 0
Shape.Text = 'X:#39'#13'#39'Y:' Text = 'X:#39'#13'#39'Y:' end object
TColorLineTool Tag = -1 Active = False AllowDrag = False Value = -
1.0000000000000000 AxisID = 2 end end ChartDef) Plot FreeGasProfile
(ChartDef object TUnitChart Left = 0 Top = 0 Width = 170 Height = 389 XUnits
= OptionDialog.PercentUnits YUnits = OptionDialog.LengthUnits XTitle =
'Volume fraction' YTitle = 'Depth' TrackerLayout = dHorizontal Logo = logoOlga
Align = alClient AllowPanning = pmNone BackColor = clWindow BackWall.Color
= clWindow BevelOuter = bvNone BorderStyle = bsSingle
BottomAxis.Axis.Width = 1 BottomAxis.Grid.Color = clSilver
BottomAxis.LabelsSeparation = 30 BottomAxis.MinorTickCount = 4 Color =
clWindow DepthAxis.Axis.Width = 1 DepthAxis.Grid.Color = clSilver
DepthAxis.LabelsSeparation = 50 LeftAxis.Axis.Width = 1 LeftAxis.Grid.Color =
clSilver LeftAxis.Inverted = True LeftAxis.LabelsSeparation = 50
LeftAxis.MinorTickCount = 4 LeftAxis.Title.Caption = 'Depth (ft)'
Legend.Alignment = laBottom Legend.CheckBoxes = True Legend.Color =
clWindow Legend.LegendStyle = lsSeries Legend.Shadow.HorizSize = 0
Legend.Shadow.VertSize = 0 Page = 1 RightAxis.Axis.Width = 1
RightAxis.Grid.Color = clSilver RightAxis.LabelsSeparation = 50
RightAxis.MinorTickCount = 4 ScaleLastPage = True TabOrder = 0
Title.Font.Color = clBlack Title.Font.Style = [fsBold] Title.Text.Strings = ( 'Free
gas') TopAxis.Axis.Width = 1 TopAxis.Grid.Color = clSilver

```

TopAxis.LabelsSeparation = 30 TopAxis.MaximumOffset = 5
 TopAxis.MinimumOffset = 5 TopAxis.MinorTickCount = 4 TopAxis.Title.Caption
 = 'Volume fraction (%)' View3D = False ExplicitWidth = 674 object
 CursorTool1: TCursorTool ShowInEditor = False Active = False Style =
 cssHorizontal end object AnnotationTool1: TAnnotationTool ShowInEditor =
 False Active = False Callout.Brush.Color = clBlack Callout.Arrow.Visible = False
 Shape.Font.Name = 'Arial Narrow' Shape.Shadow.HorizSize = 0
 Shape.Shadow.VertSize = 0 Shape.Text = 'X:#39#13#39Y:' Text =
 'X:#39#13#39Y:' end object TColorLineTool Tag = -1 Active = False
 AllowDrag = False Value = -1.0000000000000000 AxisID = 2 end end
 ChartDef) Custom plots 2 Ver 0.5 Hor 0.5 Plot PumpPressure (ChartDef object
 TUnitChart Left = 0 Top = 0 Width = 553 Height = 192 XUnits =
 OptionDialog.TimeUnits YUnits = OptionDialog.PressureUnits XTitle = 'Time'
 YTitle = 'Pressure' HorizAxis = aBottomAxis Logo = logoOlga Align = alClient
 AllowPanning = pmNone BackColor = clWindow BackWall.Color = clWindow
 BevelOuter = bvNone BorderStyle = bsSingle BottomAxis.Axis.Width = 1
 BottomAxis.Grid.Color = clSilver BottomAxis.LabelsSeparation = 30
 BottomAxis.MinorTickCount = 4 BottomAxis.Title.Caption = 'Time (min)' Color
 = clWindow DepthAxis.Axis.Width = 1 DepthAxis.Grid.Color = clSilver
 DepthAxis.LabelsSeparation = 50 LeftAxis.Axis.Width = 1 LeftAxis.Grid.Color =
 clSilver LeftAxis.LabelsSeparation = 50 LeftAxis.MaximumOffset = 5
 LeftAxis.MinimumOffset = 5 LeftAxis.MinorTickCount = 4 LeftAxis.Title.Caption
 = 'Pressure (psi)' Legend.Alignment = laBottom Legend.CheckBoxes = True
 Legend.Color = clWindow Legend.LegendStyle = lsSeries
 Legend.Shadow.HorizSize = 0 Legend.Shadow.VertSize = 0 Page = 1
 RightAxis.Axis.Width = 1 RightAxis.Grid.Color = clSilver
 RightAxis.LabelsSeparation = 50 RightAxis.MinorTickCount = 4 ScaleLastPage
 = True TabOrder = 0 Title.Font.Color = clBlack Title.Font.Style = [fsBold]
 Title.Text.Strings = ('Pump pressure') TopAxis.Axis.Width = 1
 TopAxis.Grid.Color = clSilver TopAxis.LabelsSeparation = 30
 TopAxis.MinorTickCount = 4 View3D = False ExplicitWidth = 400 ExplicitHeight
 = 250 object CursorTool1: TCursorTool ShowInEditor = False Active = False
 Style = cssVertical end object AnnotationTool1: TAnnotationTool ShowInEditor
 = False Active = False Callout.Brush.Color = clBlack Callout.Arrow.Visible =
 False Shape.Font.Name = 'Arial Narrow' Shape.Shadow.HorizSize = 0
 Shape.Shadow.VertSize = 0 Shape.Text = 'X:#39#13#39Y:' Text =
 'X:#39#13#39Y:' end object TColorLineTool Tag = -1 Active = False
 AllowDrag = False Value = -1.0000000000000000 AxisID = 0 end end
 ChartDef) Plot InfluxGasMass (ChartDef object TUnitChart Left = 0 Top = 0
 Width = 553 Height = 192 XUnits = OptionDialog.TimeUnits YUnits =
 OptionDialog.MassRateUnits XTitle = 'Time' YTitle = 'Mass rate' HorizAxis =
 aBottomAxis Logo = logoOlga Align = alClient AllowPanning = pmNone
 BackColor = clWindow BackWall.Color = clWindow BevelOuter = bvNone
 BorderStyle = bsSingle BottomAxis.Axis.Width = 1 BottomAxis.Grid.Color =
 clSilver BottomAxis.LabelsSeparation = 30 BottomAxis.MinorTickCount = 4
 BottomAxis.Title.Caption = 'Time (min)' Color = clWindow
 DepthAxis.Axis.Width = 1 DepthAxis.Grid.Color = clSilver
 DepthAxis.LabelsSeparation = 50 LeftAxis.Axis.Width = 1 LeftAxis.Grid.Color =
 clSilver LeftAxis.LabelsSeparation = 50 LeftAxis.MaximumOffset = 5
 LeftAxis.MinimumOffset = 5 LeftAxis.MinorTickCount = 4 LeftAxis.Title.Caption
 = 'Mass rate (lbm/s)' Legend.Alignment = laBottom Legend.CheckBoxes = True
 Legend.Color = clWindow Legend.LegendStyle = lsSeries
 Legend.Shadow.HorizSize = 0 Legend.Shadow.VertSize = 0 Page = 1
 RightAxis.Axis.Width = 1 RightAxis.Grid.Color = clSilver
 RightAxis.LabelsSeparation = 50 RightAxis.MinorTickCount = 4 ScaleLastPage
 = True TabOrder = 0 Title.Font.Color = clBlack Title.Font.Style = [fsBold]
 Title.Text.Strings = ('Influx from reservoir (mass rate)') TopAxis.Axis.Width =
 1 TopAxis.Grid.Color = clSilver TopAxis.LabelsSeparation = 30
 TopAxis.MinorTickCount = 4 View3D = False ExplicitWidth = 400 ExplicitHeight
 = 250 object CursorTool1: TCursorTool ShowInEditor = False Active = False
 Style = cssVertical end object AnnotationTool1: TAnnotationTool ShowInEditor
 = False Active = False Callout.Brush.Color = clBlack Callout.Arrow.Visible =
 False Shape.Font.Name = 'Arial Narrow' Shape.Shadow.HorizSize = 0


```

Shape.Shadow.VertSize = 0 Shape.Text = 'X:#39'#13'#39'Y:' Text =
'X:#39'#13'#39'Y:' end object TColorLineTool Tag = -1 Active = False
AllowDrag = False Value = -1.0000000000000000 AxisID = 0 end end
ChartDef) Hor 0.5 Plot TotalLiquidPumped (ChartDef object TUnitChart Left = 0
Top = 0 Width = 554 Height = 192 XUnits = OptionDialog.TimeUnits YUnits =
OptionDialog.LiquidRateUnits XTitle = 'Time' YTitle = 'Flowrate' HorizAxis =
aBottomAxis Logo = logoOlga Align = alClient AllowPanning = pmNone
BackColor = clWindow BackWall.Color = clWindow BevelOuter = bvNone
BorderStyle = bsSingle BottomAxis.Axis.Width = 1 BottomAxis.Grid.Color =
clSilver BottomAxis.LabelsSeparation = 30 BottomAxis.MinorTickCount = 4
BottomAxis.Title.Caption = 'Time (min)' Color = clWindow
DepthAxis.Axis.Width = 1 DepthAxis.Grid.Color = clSilver
DepthAxis.LabelsSeparation = 50 LeftAxis.Axis.Width = 1 LeftAxis.Grid.Color =
clSilver LeftAxis.LabelsSeparation = 50 LeftAxis.MaximumOffset = 5
LeftAxis.MinimumOffset = 5 LeftAxis.MinorTickCount = 4 LeftAxis.Title.Caption
= 'Flowrate (bbl/min)' Legend.Alignment = laBottom Legend.CheckBoxes =
True Legend.Color = clWindow Legend.LegendStyle = lsSeries
Legend.Shadow.HorizSize = 0 Legend.Shadow.VertSize = 0 Page = 1
RightAxis.Axis.Width = 1 RightAxis.Grid.Color = clSilver
RightAxis.LabelsSeparation = 50 RightAxis.MinorTickCount = 4 ScaleLastPage
= True TabOrder = 0 Title.Font.Color = clBlack Title.Font.Style = [fsBold]
Title.Text.Strings = ( 'Pumped volume rate') TopAxis.Axis.Width = 1
TopAxis.Grid.Color = clSilver TopAxis.LabelsSeparation = 30
TopAxis.MinorTickCount = 4 View3D = False ExplicitTop = 25 ExplicitWidth =
1067 ExplicitHeight = 364 object CursorTool1: TCursorTool ShowInEditor =
False Active = False Style = cssVertical end object AnnotationTool1:
TAnnotationTool ShowInEditor = False Active = False Callout.Brush.Color =
clBlack Callout.Arrow.Visible = False Shape.Font.Name = 'Arial Narrow'
Shape.Shadow.HorizSize = 0 Shape.Shadow.VertSize = 0 Shape.Text =
'X:#39'#13'#39'Y:' Text = 'X:#39'#13'#39'Y:' end object TColorLineTool Tag
= -1 Active = False AllowDrag = False Value = -1.0000000000000000 AxisID
= 0 end end ChartDef) Plot BottomholePressure (ChartDef object TUnitChart
Left = 0 Top = 0 Width = 554 Height = 192 XUnits = OptionDialog.TimeUnits
YUnits = OptionDialog.PressureUnits XTitle = 'Time' YTitle = 'Pressure'
HorizAxis = aBottomAxis Logo = logoOlga Align = alClient AllowPanning =
pmNone BackColor = clWindow BackWall.Color = clWindow BevelOuter =
bvNone BorderStyle = bsSingle BottomAxis.Axis.Width = 1
BottomAxis.Grid.Color = clSilver BottomAxis.LabelsSeparation = 30
BottomAxis.MinorTickCount = 4 BottomAxis.Title.Caption = 'Time (min)' Color
= clWindow DepthAxis.Axis.Width = 1 DepthAxis.Grid.Color = clSilver
DepthAxis.LabelsSeparation = 50 LeftAxis.Axis.Width = 1 LeftAxis.Grid.Color =
clSilver LeftAxis.LabelsSeparation = 50 LeftAxis.MaximumOffset = 5
LeftAxis.MinimumOffset = 5 LeftAxis.MinorTickCount = 4 LeftAxis.Title.Caption
= 'Pressure (psi)' Legend.Alignment = laBottom Legend.CheckBoxes = True
Legend.Color = clWindow Legend.LegendStyle = lsSeries
Legend.Shadow.HorizSize = 0 Legend.Shadow.VertSize = 0 Page = 1
RightAxis.Axis.Width = 1 RightAxis.Grid.Color = clSilver
RightAxis.LabelsSeparation = 50 RightAxis.MinorTickCount = 4 ScaleLastPage
= True TabOrder = 0 Title.Font.Color = clBlack Title.Font.Style = [fsBold]
Title.Text.Strings = ( 'Bottomhole pressure') TopAxis.Axis.Width = 1
TopAxis.Grid.Color = clSilver TopAxis.LabelsSeparation = 30
TopAxis.MinorTickCount = 4 View3D = False ExplicitWidth = 400 ExplicitHeight
= 250 object CursorTool1: TCursorTool ShowInEditor = False Active = False
Style = cssVertical end object AnnotationTool1: TAnnotationTool ShowInEditor
= False Active = False Callout.Brush.Color = clBlack Callout.Arrow.Visible =
False Shape.Font.Name = 'Arial Narrow' Shape.Shadow.HorizSize = 0
Shape.Shadow.VertSize = 0 Shape.Text = 'X:#39'#13'#39'Y:' Text =
'X:#39'#13'#39'Y:' end object TColorLineTool Tag = -1 Active = False
AllowDrag = False Value = -1.0000000000000000 AxisID = 0 end end
ChartDef) </PlotLayout>

```

</AbcData>

</ApplicationData>

```
</Case>
- <DocumentInfo>
  <CreatorApplication>OLGA ABC</CreatorApplication>
  <CreatorDateTime>2010-04-21T11:07:23.578</CreatorDateTime>
  <CreatorAuthor>mixkurt</CreatorAuthor>
  <LastModifiedApplication>OLGA ABC</LastModifiedApplication>
  <LastModifiedDateTime>2010-04-22T12:29:16</LastModifiedDateTime>
  <LastModifiedAuthor>mixkurt</LastModifiedAuthor>
</DocumentInfo>
</Project>
```